

PureDRI Hand Dryer



Designed to deliver three points of infection control, fast-dry hand drying and exceptional energy efficiency, the PureDRI station will substantially reduce contamination risk whilst creating cleaner, fresher smelling and more sustainable washroom environments.



Dry time
20 secs



Noise output
76dBA



Rated power
0.2kW



Running cost
£65 p/y

Airflow · Technology · Expertise

01865 882330
sales@airdri.com
airdri.com



AIRDRI PureDRI

**In-built
sanitising
technology**

**5 Year
Warranty**

**Colour
options**
Brushed
stainless steel
/ white

**CO₂ Kg
per use
0.25g**

Dimensions	270x820x100mm
Weight	9.2kg
Electrical supply	110VAC - 240VAC 50/60Hz
Current consumption	1.7A @ 115VAC / 0.9A @ 230VAC
Power consumption	0.2kW (220W)
Drying speed	20 seconds
Control system	Room sanitising: Continuous. Hand drying & sanitising: Automatic, infrared, no touch
Aperture type	Concentrated jet
Air velocity	50m/s / 112mph (100mm vertically under outlet)
Air outlet temperature	30°C at 20°C ambient
Noise level	76dBA at 1 meter (3ft) from dryer
Cover options	Brushed stainless steel
Colour options	



**Brushed Stainless Steel
/ White (as standard)**

Lamp Options	3mg Ozone bulb as standard. 0mg Non Ozone bulb available
---------------------	---

CO₂ per use: Based on CO₂ emissions from the electricity grid of the UK 2022 per use of the dryer - carbonfootprint.com

Noise output: Tested at ISVR Consulting, Southampton University Audio Labs UK

Running cost: Based on 200 washes per day, 365 days per year. The 2024 average commercial electricity cost is 20 pence per kilowatt hour

01865 882330
sales@airdri.com
airdri.com